

K REND COLOUR FILL

Water-based acrylic Filler

Backgrounds should be clean, level, dry and free from efflorescence.

For fine cracks, it is recommended that the width of the crack is widened to around 5-6 mm. This is best achieved using an electric multi-cutter with blade attachment.

Remove tip screw and end cap and attach nozzle onto cartridge.

APPLICATION

Using standard applicator's gun, apply the filler in a steady manner along the length of the crack, allowing filler to protrude out of crack. Remove the excess material using a dry sponge or cloth whilst creating a textured finish.

It is recommended to build the filler up in layers, allowing each layer to dry before applying the next. After addition of final layer, allow the filler to fully cure for about 12- 24 hours (depending on thickness and weather).

Protect the freshly applied filler from rain and from drying too fast; drying times may be prolonged by lower temperatures and/or high humidity.

Please refer to application video on our website for further guidance.

Kilwaughter Minerals Ltd are a ISO9001 & ISO14001 registered company.

IF THESE INSTRUCTIONS ARE NOT FOLLOWED CLOSELY, A SATISFACTORY FINISH MAY NOT BE ACHIEVED AND KILWAUGHTER MINERALS LTD WILL ACCEPT NO RESPONSIBILITY.

STORAGE

Cartridges should be further protected to prevent damp causing caking of the product. Shelf life is approximately one year if stored in original, sealed containers and protected against frost and away from direct sunlight. It is important to note that all K Rend products are non-refundable.

APPLICATION CONSIDERATIONS

K Rend products have a working temperature range of 5°C – 35°C. Do not apply in conditions of strong sunshine or wind; do not apply onto frozen surfaces. Drying conditions will vary accordingly to wind, temperature and humidity. Protection from rain and frost should be provided for a minimum of 48 hours after application.

MATERIAL SAFETY DATA SHEET COSHH

Wear suitable eye protection.

Avoid contact with skin.

P103: Keep out of reach of children.

P280: Wear protective gloves, eye protection

P305: IF IN EYES rinse immediately with plenty of water and seek medical advice

After contact with eyes - wash thoroughly with clean water for at least 15 minutes. Seek medical advice.

After contact with skin - wash thoroughly with soap and water.

Manufactured by Kilwaughter Minerals Ltd, 9 Starbog Road, Larne, Co. Antrim, BT40 2TJ. Tel: 028 2826 0766

Refer to full Material Safety Data Sheet which is available upon request.