

Product Data Sheet

STANDARD UF BASE

K Rend Standard UF Base is a high quality all purpose sprayable base coat with excellent workability qualities, designed to be used over block work as a primary coat for K Rend finishes and is ideal as the background for thin coat acrylic finishes.

All K Rend base coats are polymer modified and cement based to ensure flexibility and strength. Scratch coats require only the addition of water and 5 minutes mixing time. Normally applied in one coat as a backing for K Rend finishes. rule off to a flat finish and scratch lightly to provide a key for the next coat.

Coverage:

1.8kg / mm thick / sq m

Require:

14-18kg / sq m approx.
nominal 8-10mm thickness

In some cases, the incorporation of K Rend scrim cloth reinforcement is advised. For work on unusual substrates always seek technical advice.

Support Backings

- K Rend Standard UF Base can be used over block work masonry or stone backgrounds
- For insulation concrete refurbishment work or any other unusual substrate seek technical advice

Application

- Mix for at least 5 minutes to break down additives
- Add 5-6 litres of clean water per 25kg sack
- Can be spray machine applied

Kitemark Classifications



Compressive strength: CS IV

Capillary Water Absorption Category: W2

Thermal Conductivity: P=50% - 0.43

In line with our policy of continuous product development, we reserve the right to change technical data without notice.



Kilwaughter Minerals Ltd

For UK Sales

9 Starbog Rd, Lame, Co. Antrim, N. Ireland, BT40 2TJ
Tel: 028 2826 0766 Fax: 028 2826 0136
Email: Sales@K-Rend.co.uk
www.K-Rend.co.uk

For ROI Sales

Classis, Ovens, Co. Cork, Ireland
Tel: 021 4872733 Fax: 021 4871705
Email: Sales@K-Rend.co.uk
www.K-Rend.co.uk